7		6		5 4	3	
	ITEM NO.	PART NUMBER	Rev.	DESCRIPTION	Material	
]	WP-20BF*15	-	WP BASE, W/PCB BOSSES, MTG FLANGES	POLYCARBONATE	LIC
	2	WP-20C*15	-	WP COVER ONLY, W/GASKET	POLYCARBONATE	LIC
	3	SCREWS-SSM4-20-4	-	ASSEMBLY SCREWS, 4 PACK		
	3.1	SCREWS-SSM4-20	-	M4X0.7 X 20mm OAL, PHILLIPS DRIVE MACHINE SCREW	STAINLESS STEEL	

0

D


С


В


А


8


8











SECTION A-A

 \square

(3.1


2

1


←(1.177)→


WP-20BF*15-PCB-PCB TEMPLATE FOR WP-20BF*15 REF. ONLY


									UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN: INCHES[mm] TOLERANCES: ANGULAR: ±2°	PART NO WP-20F*	
ED TO NEMA 1, 2, 4, 4X, 12, 13. X SPECIFICATIONS (UL FILE E194432). RE: -40°C TO 120°C									TWO PLACE DECIMAL: ±.030 THREE PLACE DECIMAL: ±.015 PRINTED GRAPHICS: ±.010 PROPRIETARY AND CONFIDENTIAL	MATERIA	١L
									THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF POLYCASE. ANY REPRODUCTION IN PART	FLAME RAUL94-HB	
			REV.	DESCRIPTION	ZONE	BV	APPR'D	DATE	OR AS A WHOLE WITHOUT THE WRITTEN		N/
			KEV.			DI	AFEKD	DAIE	PERMISSION OF POLYCASE IS PROHIBITED.	DRAWN	D.
	1			REV	<u>/ISIONS</u>				CAD FILE: WP-20F+15	CHECKED	<u> </u>
7	6			5	Ť		4		3		




NOTES: 1. ENCLOSURE DESIGNED 2. UL LISTED TO UL508-4X 3. SERVICE TEMPERATURE









Enable 3D View