TOLERANCE CHART													
DIMENSION RANGE	0	.039	.118	.236	.394	.591	.866	1.181	1.575	2.087	2.756	3.543	4.724
	.039	.118	.236	.394	.591	.866	1.181	1.575	2.087	2.756	3.543	4.724	6.299
TOOL DEPENDENT	±.007	±.007	±.008	±.008	±.009	±.010	±.011	±.012	±.013	±.015	±.017	±.020	±.024
NON-TOOL DEPENDENT	±.003	±.004	±.004	±.004	±.005	±.006	±.007	±.008	±.009	±.011	±.013	±.016	±.020





SECTION A-A

PART NUMBER: KT-35SC0
MATERIAL SPEC: /ABS/PA765/BK
MATERIAL: ABS
COLOR: BLACK
FLAME RATING: UL94V-0



PART NUMBER: KT-35SC0*01
MATERIAL SPEC: /ABS/PA765/GY
MATERIAL: ABS
COLOR: GRAY
FLAME RATING: UL94V-0



PART NUMBER: KT-35SC0*03
MATERIAL SPEC: /ABS/PA765/BO
MATERIAL: ABS
COLOR: BONE
FLAME RATING: UL94V-0



PART NUMBER: KT-35SC0-NOR
MATERIAL SPEC: /PPO/SE100X/BK
MATERIAL: PPE+PS
COLOR: BLACK
FLAME RATING: UL94V-1



NOTES:
1. REFER TO SOLID MODEL FOR COMPLETE PART DEFINITION.
2. (INSPECTION DIMENSION)
3. EJECTOR PINS TO BE FLUSH ±.010
4. FLASH .005 MAX
5. GATE TO BE REMOVED FLUSH ±.015

REVISIONS					
REV.	DESCRIPTION	ZONE	BY	APPR'D	DATE

UNLESS OTHERWISE SPECIFIED:
DIMENSIONS ARE IN: INCHES[mm]
TOLERANCES: ANGULAR: ±2°
TWO PLACE DECIMAL: ±-
THREE PLACE DECIMAL: ±-
PRINTED GRAPHICS: ±.010

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF POLYCASE. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF POLYCASE IS PROHIBITED.

CAD FILE: KT-35SC0

PART NO.
AS NOTED

MATERIAL
-

FLAME RATING
-

	NAME	DATE
DRAWN	D.M.F.	10/4/2023
CHECKED	B.M.B.	10/4/2023

SIZE **B**

COVER: RECESSED SMOOTH

REV **0**

SCALE: 1:1

SHEET 1 OF 1

polycase
1305 CHESTER IND. PARKWAY AVON, OHIO 44011-1083 U.S.A.
PH#: 1-800-248-1233, 440-934-0444 FAX#: 440-934-0088