

TOLERANCE CHART													
DIMENSION RANGE	0	.039	.118	.236	.394	.591	.866	1.181	1.575	2.087	2.756	3.543	4.724
	.039	.118	.236	.394	.591	.866	1.181	1.575	2.087	2.756	3.543	4.724	6.299
TOOL DEPENDENT	±.007	±.007	±.008	±.008	±.009	±.010	±.011	±.012	±.013	±.015	±.017	±.020	±.024
NON-TOOL DEPENDENT	±.003	±.004	±.004	±.004	±.005	±.006	±.007	±.008	±.009	±.011	±.013	±.016	±.020


PART NUMBER: KT-40SC0
MATERIAL SPEC: /ABS/PA765/BK
MATERIAL: ABS
COLOR: BLACK
FLAME RATING: UL94V-0

PART NUMBER: KT-40SC0*01
MATERIAL SPEC: /ABS/PA765/GY
MATERIAL: ABS
COLOR: GRAY
FLAME RATING: UL94V-0

PART NUMBER: KT-40SC0*03
MATERIAL SPEC: /ABS/PA765/BO
MATERIAL: ABS
COLOR: BONE
FLAME RATING: UL94V-0

- NOTES:
1. REFER TO SOLID MODEL FOR COMPLETE PART DEFINITION.
 2. (INSPECTION DIMENSION)
 3. EJECTOR PINS TO BE FLUSH ±.010
 4. FLASH .005 MAX
 5. GATE TO BE REMOVED FLUSH ±.015

REV.	DESCRIPTION	ZONE	BY	APPR'D	DATE
REVISIONS					

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN: INCHES[mm] TOLERANCES: ANGULAR: ±2° TWO PLACE DECIMAL: ± THREE PLACE DECIMAL: ± PRINTED GRAPHICS: ±-			PART NO. AS NOTED		<div><div>polycase</div><div>1305 CHESTER IND. PARKWAY AVON, OHIO 44011-1083 U.S.A. PH#: 1-800-248-1233, 440-934-0444 FAX#: 440-934-0088</div></div>						
			MATERIAL -								
PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF POLYCASE. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF POLYCASE IS PROHIBITED. CAD FILE: KT-40SC0			FLAME RATING -		SIZE B		COVER		REV 0		
				NAME	DATE						
			DRAWN	D.M.F.	10/4/2023	SCALE: 1:1				SHEET 1 OF 1	
			CHECKED	B.M.B.	10/4/2023						