



- NOTES:
1. REFER TO SOLID MODEL FOR COMPLETE PART DEFINITION.
  2. (INSPECTION DIMENSION)
  3. EJECTOR PINS TO BE FLUSH ±.010
  4. FLASH .005 MAX
  5. GATE TO BE REMOVED FLUSH ±.015

DIMENSION RANGE	0	.039	.118	.236	.394	.591	.866	1.181	1.575	2.087	2.756	3.543	4.724	6.299
	.039	.118	.236	.394	.591	.866	1.181	1.575	2.087	2.756	3.543	4.724	6.299	7.874
TOOL DEPENDENT	±.007	±.007	±.008	±.008	±.009	±.010	±.011	±.012	±.013	±.015	±.017	±.020	±.024	±.028
NON-TOOL DEPENDENT	±.003	±.004	±.004	±.004	±.005	±.006	±.007	±.008	±.009	±.011	±.013	±.016	±.020	±.024

TOLERANCE CHART

REV.	DESCRIPTION	ZONE	BY	APPR'D	DATE
1	LENGTH/WIDTH TOLERANCE WAS +/- .005	B6, C4	D.M.F.	B.M.B.	12/18/2023
0	UPDATED FOR NEW MOLD		D.M.F.	B.M.B.	12/1/2022
REVISIONS					

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN: INCHES[mm] TOLERANCES: ANGULAR: ±2° TWO PLACE DECIMAL: ±.010 THREE PLACE DECIMAL: ±.005 PRINTED GRAPHICS: ±.010		PART NO. SL-64C-R		<div><p>1305 CHESTER IND. PARKWAY AVON, OHIO 44011-1083 U.S.A. PH#: 1-800-248-1233, 440-934-0444 FAX#: 440-934-0088</p></div>			
PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF POLYCASE. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF POLYCASE IS PROHIBITED. CAD FILE: SL-64C-R		MATERIAL ABS					
FLAME RATING UL94V-0			SIZE <b>B</b>	COVER: RECESSED SMOOTH			REV <b>1</b>
DRAWN CHECKED		NAME D.M.F.		DATE 8/15/2022 12/31/2999		SCALE: 1:1	
						SHEET 1 OF 1	