



TOLERANCE CHART																					
DIMENSION RANGE	0	.039	.118	.236	.394	.591	.866	1.181	1.575	2.087	2.756	3.543	4.724	6.299	7.874	9.843	12.402	15.748	19.685	24.803	31.496
	.039	.118	.236	.394	.591	.866	1.181	1.575	2.087	2.756	3.543	4.724	6.299	7.874	9.843	12.402	15.748	19.685	24.803	31.496	39.37
TOOL DEPENDENT	±.007	±.007	±.008	±.008	±.009	±.010	±.011	±.012	±.013	±.015	±.017	±.020	±.024	±.028	±.035	.043	.051	.063	.079	.098	.118
NON-TOOL DEPENDENT	±.003	±.004	±.004	±.004	±.005	±.006	±.007	±.008	±.009	±.011	±.013	±.016	±.020	±.024	±.031	.039	.047	.059	.075	.094	.114

PART NUMBER: VM-24BMB19V*14
MATERIAL: ABS
MATERIAL SPEC: /ABS/PA765/WH
COLOR: WHITE
FLAME RATING: UL94-5VA

PART NUMBER: VM-24BMB19V*03
MATERIAL: ABS
MATERIAL SPEC: /ABS/PA765/BO
COLOR: BONE
FLAME RATING: UL94-5VA

PART NUMBER: VM-24BMB19V
MATERIAL: ABS
MATERIAL SPEC: /ABS/PA765/BK
COLOR: BLACK
FLAME RATING: UL94-5VA

- NOTES:
- REFER TO SOLID MODEL FOR COMPLETE PART DEFINITION.
 - (INSPECTION DIMENSION)
 - GATE FLUSH ±.015
 - FLASH .005 MAX

0	ADDED VM-24BMB19V*14		Douglas French	3-27-2024
REV.	COMMENT	ZONE	REVISED BY	MODIFICATION DATE
REVISIONS				

UNLESS OTHERWISE SPECIFIED:
DIMENSIONS ARE IN: INCHES [mm]
TOLERANCES: ANGULAR: ±2°
TWO PLACE DECIMAL: ±
THREE PLACE DECIMAL: ±
PRINTED GRAPHICS: ±.010

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS
DRAWING IS THE SOLE PROPERTY OF
POLYCASE. ANY REPRODUCTION IN PART
OR AS A WHOLE WITHOUT THE WRITTEN
PERMISSION OF POLYCASE IS PROHIBITED.
CAD FILE: VM-24BMB19V

PART NO.
AS NOTED
MATERIAL

FLAME RATING

DRAWN	NAME	DATE
CHECKED	-	3/27/2024

polycase
1305 CHESTER IND. PARKWAY AVON, OHIO 44011-1083 U.S.A.
PH#: 1-800-248-1233, 440-934-0444 FAX#: 440-934-0088

SIZE	BASE: ONE 9V BATTERY	REV
B		0
SCALE: 1:1	SHEET 1 OF 1	