



BOM Table						
ITEM NO.	PART NUMBER	Rev.	Description	Material	Color	QTY.
1	WQ-70S-02	-	Hinged Nema Enclosure-Outdoor Use			1
1.1	WQ-70B-02	-	BASE	GFR10/PC	GRAY	1
1.2	WQ-70C-02	-	COVER W/GASKET	PC	GRAY	1
1.3	WQ-76L-01	-.01	LATCH ASSEMBLY	-	-	2
1.4	WQ-PIN-02	-	HINGE PIN	SST	-	2
2	SCREWS-026-004	-	SCREWS, 4 PACK			1
2.1	SCREWS-026	-	M5X0.8 x 10mm CROSS TRUSS HEAD SCREW			4










WQ-70-02
UL LISTED: UL508-4X
SERVICE TEMP: -40°C to 95°C
FLAME RATING: 5VA
Outdoor Suitability: UL746C F1

BOM Table						
ITEM NO.	PART NUMBER	Rev.	Description	Material	Color	QTY.
1	WQ-70S-03	-	Hinged Nema Enclosure-Outdoor Use			1
1.1	WQ-70B-02	-	BASE	GFR10/PC	GRAY	1
1.2	WQ-70C-03	-	COVER W/GASKET	PC	CLEAR	1
1.3	WQ-76L-01	-.01	LATCH ASSEMBLY	-	-	2
1.4	WQ-PIN-02	-	HINGE PIN	SST	-	2
2	SCREWS-026-004	-	SCREWS, 4 PACK			1
2.1	SCREWS-026	-	M5X0.8 x 10mm CROSS TRUSS HEAD SCREW			4




WQ-70-03
UL LISTED: UL508-4X
SERVICE TEMP: -40°C to 95°C
FLAME RATING: 5VA
Outdoor Suitability: UL746C F1

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN: INCHES[mm] TOLERANCES: ANGULAR: ±.° TWO PLACE DECIMAL: ±. THREE PLACE DECIMAL: ±. PRINTED GRAPHICS: ±.		PART NO. WQ-70		MATERIAL		FLAME RATING 5VA		SIZE C		Hinged Nema Enclosure, Outdoor Use, with Screw Kit		REV -	
PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF POLYCASE. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF POLYCASE IS PROHIBITED. CAD FILE: WQ-70		NAME D.M.F. C.C.B.											



TOP VIEW WITH COVER HIDDEN



SECTION A-A

REV.	DESCRIPTION	ZONE	BY	APPR'D	DATE
REVISIONS					