



NOTES:

1. INCLUDES .031 CLEARANCE WITH INSIDE WALLS, BLADES, GROUND PIN, AND SCREW TOWERS.
2. AN OPTIONAL METHOD OF CONNECTING PCB TO BLADES AND GROUND PIN IS TO DECREASE THE CLEARANCE AROUND THE BLADES AND GROUND PIN AND SOLDER THEM DIRECTLY TO THE PCB.

| | | | | |
|---|--|-----------------------|-----------------------|---|
| UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN: INCHES[mm] TOLERANCES: ANGULAR: ±2° TWO PLACE DECIMAL: ±.010 THREE PLACE DECIMAL: ±.005 PRINTED GRAPHICS: ±.010 | | PART NO. B2405-PCB | |  POLYCASE™ YOUR PERFECT FIT 1305 CHESTER IND. PARKWAY AVON, OHIO 44011-1083 U.S.A. PH#: 1-800-248-1233, 440-934-0444 FAX#: 440-934-0088 |
| PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF POLYCASE. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF POLYCASE IS PROHIBITED. CAD FILE: B2405-PCB | | PRODUCT - | | |
| CLIENT - | | SIZE A | TITLE: PCB Drawing | REV - |
| DRAWN D.M.F. 3/11/2009 | | SCALE: 1:1 | |  SHEET 1 OF 1 |
| CHECKED B.M.B. 3/25/2009 | | | | |

| ZONE | REV. | DESCRIPTION | BY | APPR'D | DATE |
|-----------|------|-------------|----|--------|------|
| REVISIONS | | | | | |

5

4

3

2

1